

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 September 2003 (12.09.2003)


PCT

(10) International Publication Number
WO 03/074163 A1

- (51) International Patent Classification⁷: B01F 3/04, 7/16
- (21) International Application Number: PCT/CA03/00292
- (22) International Filing Date: 3 March 2003 (03.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/361,281 4 March 2002 (04.03.2002) US
- (71) Applicant (*for all designated States except US*): CYMAT CORP. [CA/CA]; 6320-2 Danville Road, Mississauga, Ontario L5T 2L7 (CA).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): NICHOL, Scott [CA/CA]; 2 Elma Street, Etobicoke, Ontario M8V 1X8 (CA). MANLEY, Richard, G. [CA/CA]; 5 Golden Gate Drive, Brampton, Ontario L6S 2K5 (CA).
- (74) Agents: CHARI, Santosh, K. et al.; McCarthy Tetrauli LLP, Suite 4700, P.O. Box 48, 66 Wellington Street West, Toronto-Dominion Bank Tower, Toronto, Ontario M5K 1E6 (CA).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: SEALED IMPELLER FOR PRODUCING METAL FOAM AND SYSTEM AND METHOD THEREFOR



(57) Abstract: A system for producing a metal foam comprises a bath containing a molten metal, a rotating shaft or impeller extending through the base of the bath into, and submerged in the molten metal, and a gas discharge nozzle provided on the submerged end of the shaft. The opposite end of the shaft is connected to a gas supply line and the shaft is rotated with a motor. A seal is provided at the opening in the base of the bath for preventing leakage of the molten metal there-through.

WO 03/074163 A1